PH, PA-Series, Hydraulic Hand Pump

PH, PA-系列,手動/鋁制泵浦

PH-Series, internal pressure relief valve for overload protection

Two-speed operation on most models reduces handle strokes by as much as 78% over single speed pumps

Handle lock and lightweight construction for easy carrying

Integral 4-way valve on PH-464 for operation of double-acting cylinders

PH-392 Durable glass-filled nylon reservoir and nylon encapsulated aluminum pump base for maximum corrosion resistance

PH-Series with large oil capacities to power a wide range of cylinders or tools

PA-Series, Aluminuim Hand Pump

Model No.	Pump Type	Oil Capacity (cm3)	Pressure		Output Flow Rate		Dimension			Weight
			No load	Load	No load	Load	٦	W	Н	(kg)
			(Bar)		(cc)		(mm)	(mm)	(mm)	
PA-800	Single Speed	700	14	700	14.9	3.1	300	140	150	3.3
PA-1300		1300	14	700	14.9	3.1	510	140	150	4.6
PH-1200		1200	14	700	15.5	2.8	536	160	142	9
PH-3000		3000	14	700	15.5	2.8	536	160	142	13
PH-392		900	13	700	11.26	2.47	522	533	177	4.1
PH-462		7423	14	700	126.6	4.75	742	308	270	27.7
PH-464	Two Speed	7423	14	700	126.6	4.75	742	308	270	27.7